




HYDROMATIK
connections par excellence

Metric Bite Type Fittings

TR - TEE REDUCERS TR |



Part No.	Series	TUBE O.D 1	TUBE O.D 2	TUBE O.D 3	I1	I2	I3	S1	S2	S3	S4
TR 06/08/06 L	Light-250 Bar	6	8	6	14	14	14	14	17	14	12
TR 08/06/08 L	Light-250 Bar	8	6	8	14	14	14	17	14	17	12
TR 06/10/06 L	Light-250 Bar	6	10	6	15	15	15	14	19	14	14
TR 08/10/08 L	Light-250 Bar	8	10	8	15	15	15	17	19	17	14
TR 10/06/10 L	Light-250 Bar	10	6	10	15	15	15	19	14	19	14
TR 10/08/10 L	Light-250 Bar	10	8	10	15	15	15	19	17	19	14
TR 10/10/06 L	Light-250 Bar	10	10	6	15	15	15	19	19	14	14
TR 08/12/08 L	Light-250 Bar	8	12	8	17	17	17	17	22	17	17
TR 12/06/12 L	Light-250 Bar	12	6	12	17	17	17	22	14	22	17

TR 12/08/08 L	Light-250 Bar	12	8	8	17	17	17	22	17	17	17
TR 12/08/12 L	Light-250 Bar	12	8	12	17	17	17	22	17	22	17
TR 12/10/10 L	Light-250 Bar	12	10	10	17	17	17	22	19	19	17
TR 12/10/12 L	Light-250 Bar	12	10	12	17	17	17	22	19	22	17
TR 12/12/10 L	Light-250 Bar	12	12	10	17	17	17	22	22	19	17
TR 10/15/10 L	Light-250 Bar	10	15	10	21	21	21	19	27	19	19
TR 12/15/12 L	Light-250 Bar	12	15	12	21	21	21	22	27	22	19
TR 15/06/15 L	Light-250 Bar	15	6	15	21	21	21	27	14	27	19
TR 15/10/15 L	Light-250 Bar	15	10	15	21	21	21	27	19	27	19
TR 15/12/12 L	Light-250 Bar	15	12	12	21	21	21	27	22	22	19
TR 15/12/15 L	Light-250 Bar	15	12	15	21	21	21	27	22	27	19
TR 15/15/12 L	Light-250 Bar	15	15	12	21	21	21	27	27	22	19
TR 12/18/12 L	Light-160 Bar	12	18	12	24	24	23.5	22	32	22	24
TR 18/10/10 L	Light-160 Bar	18	10	10	23.5	24	24	32	19	19	24

TR 18/10/18 L	Light-160 Bar	18	10	18	23.5	23.5	24	32	19	32	24
TR 18/12/18 L	Light-160 Bar	18	12	18	23.5	23.5	24	32	22	32	24
TR 18/15/18 L	Light-160 Bar	18	15	18	23.5	23.5	24	32	27	32	24
TR 18/18/10 L	Light-160 Bar	18	18	10	23.5	24	23.5	32	32	19	24
TR 22/10/22 L	Light-160 Bar	22	10	22	27.5	27.5	28	36	19	36	27
TR 22/12/22 L	Light-160 Bar	22	12	22	27.5	27.5	28	36	22	36	27
TR 22/15/15 L	Light-160 Bar	22	15	15	27.5	28	28	36	27	27	27
TR 22/15/22 L	Light-160 Bar	22	15	22	27.5	27.5	28	36	27	36	27
TR 22/18/18 L	Light-160 Bar	22	18	18	27.5	27.5	27.5	36	32	32	27
TR 22/18/22 L	Light-160 Bar	22	18	22	27.5	27.5	27.5	36	32	36	27
TR 22/22/18 L	Light-160 Bar	22	22	18	27.5	27.5	27.5	36	36	32	27
TR 22/10/22 L	Light-160 Bar	22	10	22	27.5	27.5	28	36	19	36	27
TR 22/12/22 L	Light-160 Bar	22	12	22	27.5	27.5	28	36	22	36	27
TR 22/15/15 L	Light-160 Bar	22	15	15	27.5	28	28	36	27	27	27

TR 22/15/22 L	Light-160 Bar	22	15	22	27.5	27.5	28	36	27	36	27
TR 22/18/18 L	Light-160 Bar	22	18	18	27.5	27.5	27.5	36	32	32	27
TR 22/18/22 L	Light-160 Bar	22	18	22	27.5	27.5	27.5	36	32	36	27
TR 22/22/18 L	Light-160 Bar	22	22	18	27.5	27.5	27.5	36	36	32	27
TR 28/10/28 L	Light-100 Bar	28	10	28	30.5	30.5	31	41	19	41	36
TR 28/12/28 L	Light-100 Bar	28	12	28	30.5	30.5	31	41	22	41	36
TR 28/15/28 L	Light-100 Bar	28	15	28	30.5	30.5	31	41	27	41	36
TR 28/18/28 L	Light-100 Bar	28	18	28	30.5	30.5	30.5	41	32	41	36
TR 28/22/22 L	Light-100 Bar	28	22	22	30.5	30.5	30.5	41	36	36	36
TR 28/22/28 L	Light-100 Bar	28	22	28	30.5	30.5	30.5	41	36	41	36
TR 10/06/10 S	Heavy-630 Bar	10	6	10	17.5	17.5	18	22	17	22	17
TR 12/08/08 S	Heavy-630 Bar	12	8	8	21.5	22	22	24	19	19	17
TR 12/08/12 S	Heavy-630 Bar	12	8	12	21.5	21.5	22	24	19	24	17
TR 12/10/12 S	Heavy-630 Bar	12	10	12	21.5	21.5	21.5	24	22	24	17

TR 12/16/12 S	Heavy-400 Bar	12	16	12	25.5	25.5	24.5	24	30	24	24
TR 16/06/16 S	Heavy-400 Bar	16	6	16	24.5	24.5	26	30	17	30	24
TR 16/08/16 S	Heavy-400 Bar	16	8	16	24.5	24.5	26	30	19	30	24
TR 16/10/16 S	Heavy-400 Bar	16	10	16	24.5	24.5	25.5	30	22	30	24
TR 16/12/16 S	Heavy-400 Bar	16	12	16	24.5	24.5	25.5	30	24	30	24
TR 16/20/16 S	Heavy-400 Bar	16	20	16	28.5	28.5	26.5	30	36	30	27
TR 20/10/20 S	Heavy-400 Bar	20	10	20	26.5	26.5	29.5	36	22	36	27
TR 20/12/20 S	Heavy-400 Bar	20	12	20	26.5	26.5	29.5	36	24	36	27
TR 20/16/20 S	Heavy-400 Bar	20	16	20	26.5	26.5	28.5	36	30	36	27
TR 20/25/20 S	Heavy-400 Bar	20	25	20	31.5	31.5	30	36	46	36	36
TR 25/16/25 S	Heavy-400 Bar	25	16	25	30	30	33.5	46	30	46	36
TR 25/20/25 S	Heavy-400 Bar	25	20	25	30	30	31.5	46	36	46	36
TR 25/30/25 S	Heavy-400 Bar	25	30	25	37	37	35.5	46	50	46	41

Dimensions given approx. Fig. with tightened nut.

Part No. Given refers to complete assembly - Steel Part