




HYDROMATIK
connections par excellence

Metric Bite Type Fittings

GE-N - STRAIGHT MALE STUD COUPLING GE-N | Taper
Male Thread G - NPT



Part No.	Series	Tube OD	i	l1	S1	S2	G - NPT
GE 06 LN	Light-250 Bar	6	10	18	12	14	G 1/8-27
GE 06 LN	Light-250 Bar	6	15.1	23	17	14	G 1/4-18
GE 08 LN	Light-250 Bar	8	15.1	23	14	17	G 1/4-18
GE 10 LN	Light-250 Bar	10	15.1	24	14	19	G 1/4-18
GE 10 LN	Light-250 Bar	10	15.1	24	19	19	G 3/8-18
GE 12 LN	Light-250 Bar	12	15.1	25	19	22	G 1/4-18
GE 12 LN	Light-250 Bar	12	19.98	25	19	22	G 3/8-18
GE 12 LN	Light-250 Bar	12	19.98	30	22	22	G 1/2-14
GE 15 LN	Light-250 Bar	15	19.8	31	24	27	G 1/2-14
GE 18 LN	Light-160 Bar	18	19.8	31.5	27	32	G 1/2-14
GE 22 LN	Light-160 Bar	22	20.5	33.5	32	36	G 3/4-14
GE 28 LN	Light-100 Bar	28	25	39.5	41	41	G 1-11.5
GE 35 LN	Light-100 Bar	35	26	40.5	46	50	G 1.1/4-11.5

GE 42 LN	Light-100 Bar	42	26	42	55	60	G 1.1/2-11.5
GE 06 SN	Heavy-630 Bar	6	15.1	26	17	17	G 1/4-18
GE 08 SN	Heavy-630 Bar	8	15.1	28	17	19	G 1/4-18
GE 10 SN	Heavy-630 Bar	10	15.1	27.5	19	22	G 1/4-18
GE 10 SN	Heavy-630 Bar	10	15.1	27.5	19	22	G 3/8-18
GE 12 SN	Heavy-630 Bar	12	15.1	29.5	22	24	G 1/4-18
GE 12 SN	Heavy-630 Bar	12	15.1	29.5	22	24	G 3/8-18
GE 12 SN	Heavy-630 Bar	12	19.98	34.5	22	24	G 1/2-14
GE 14 SN	Heavy-400 Bar	14	19.98	36	24	27	G 1/2-14
GE 16 SN	Heavy-400 Bar	16	19.98	35.5	27	30	G 1/2-14
GE 20 SN	Heavy-400 Bar	20	20.5	37.5	32	36	G 3/4-14
GE 25 SN	Heavy-400 Bar	25	25	45	41	46	G 1-11.5
GE 30 SN	Heavy-250 Bar	30	25.6	46.5	46	50	G 1.1/4-11.5
GE 38 SN	Heavy-250 Bar	38	26	49	55	60	G 1.1/2-11.5

Dimensions given approx. Fig. with tightened nut.

Part No. Given refers to complete assembly - Steel Part