





**HYDROMATIK**  
connections par excellence

## Metric Bite Type Fittings

### VKA - BLANKING PLUG WITH NUT VKA |



Part No.	D1	L1	S2	O' RING
VKA 06-L	6	18.5	14	4 X 1.5
VKA 08-L	8	18.5	17	6 X 1.5
VKA 10-L	10	20	19	7.5 X 1.5
VKA 12-L	12	20.5	22	9 X 1.5
VKA 15-L	15	20.5	27	12 X 2
VKA 18-L	18	22.5	32	15 X 2
VKA 22-L	22	25	36	20 X 2
VKA 28-L	28	25.5	41	26 X 2
VKA 35-L	35	30	50	32 X 2.5
VKA 42-L	42	30	60	38 X 2.5
VKA 06-S	6	18.5	17	4 X 1.5
VKA 08-S	8	18.5	19	6 X 1.5
VKA 10-S	10	20	22	7.5 X 1.5
VKA 12-S	12	20.5	24	9 X 1.5
VKA 14-S	14	22.5	27	10 X 2

VKA 16-S	16	23.5	30	12 X 2
VKA 20-S	20	28.5	36	16.3 X 2.4
VKA 25-S	25	29	46	20.3 X 2.4
VKA 30-S	30	30.5	50	25.3 X 2.4
VKA 38-S	38	33	60	33.3 X 2.4

Dimensions given approx. fig. with tightened nut

Temp range without pressure reductions

for 'O' Ring sealing of NBR (buna N- Std) -35° to +100° C, for FPM

(Viton - On request) -25° to +120° C.