





HYDROMATIK
connections par excellence

Metric Bite Type Fittings

SHP-M-ED - SOCKET HEAD PLUG WITH ELASTOMERIC SEAL SHP-M-ED | METRIC Threads - M



Part No.	M	d3	L1	L2	S1
SHP M10 ED	M10 X 1.0	14	12	8	5
SHP M12 ED	M12 X 1.5	17	17	12	6
SHP M14 ED	M14 X 1.5	19	17	12	6
SHP M16 ED	M16 X 1.5	21.9	17	12	8
SHP M18 ED	M18 X 1.5	23.9	17	12	8
SHP M20 ED	M20 X 1.5	25.9	19	14	10
SHP M22 ED	M22 X 1.5	27	19	14	10
SHP M26 ED	M26 X 1.5	31.9	21	16	12
SHP M27 ED	M27 X 2.0	32	21	16	12
SHP M33 ED	M33 X 2.0	39.9	22.5	16	17
SHP M42 ED	M42 X 2.0	49.9	22.5	16	22
SHP M48 ED	M48 X 2.0	55	22.5	16	24

Dimensions given approx. fig. with tightened nut

Temp range without pressure reductions

for 'O' Ring sealing of NBR (buna N- Std) -35° to $+100^{\circ}$ C, for FPM

(Viton - On request) -25° to $+120^{\circ}$ C.