





HYDROMATIK
connections par excellence

Metric Bite Type Fittings

FEGE-R - FEMALE STUD ADAPTOR WITH SWIVEL NUT

FEGE-R |



Part No.	Series	Tube OD D1	G	L1	L	S1	S2	M	O' Ring
FEGE 06-LR	Light-250 Bar	6	1/8	12	36	14	14	M12 X 1.5	4 X 1.5
FEGE 08-LR	Light-250 Bar	8	1/4	17	41	19	17	M14 X 1.5	6 X 1.5
FEGE 10-LR	Light-250 Bar	10	1/4	17	41	19	19	M16 X 1.5	7.5 X 1.5
FEGE 12-LR	Light-250 Bar	12	3/8	17	43	24	22	M18 X 1.5	9 X 1.5
FEGE 15-LR	Light-250 Bar	15	1/2	20	48.5	30	27	M22 X 1.5	12 X 2
FEGE 18-LR	Light-160 Bar	18	1/2	20	48.5	30	32	M26 X 1.5	15 X 2
FEGE 22-LR	Light-160 Bar	22	3/4	22	53	36	36	M30 X 2.0	20 X 2
FEGE 28-LR	Light-100 Bar	28	1	24.5	57	41	41	M36 X 2.0	26 X 2
FEGE 35-LR	Light-100 Bar	35	1 1/4	26.5	67	55	50	M42 X 2.0	32 X 2.5
FEGE 42-LR	Light-100 Bar	42	1 1/2	28.5	69.5	60	60	M52 X 2.0	38 X 2.5
FEGE 06-SR	Heavy-630 Bar	6	1/4	17	41	19	17	M14 X 1.5	4 X 1.5
FEGE 08-SR	Heavy-630 Bar	8	1/4	17	41	19	19	M16 X 1.5	6 X 1.5
FEGE 10-SR	Heavy-630 Bar	10	3/8	17	44	24	22	M18 X 1.5	7.5 X 1.5

FEGE 12-SR	Heavy-630 Bar	12	3/8	17	44	24	24	M20 X 1.5	9 X 1.5
FEGE 14-SR	Heavy-630 Bar	14	1/2	20	51	30	27	M22 X 1.5	10 X 2
FEGE 16-SR	Heavy-400 Bar	16	1/2	20	51	30	30	M24 X 1.5	12 X 2
FEGE 20-SR	Heavy-400 Bar	20	3/4	22	58.5	36	36	M30 X 2.0	16.3 X 2.4
FEGE 25-SR	Heavy-400 Bar	25	1	24.5	64	41	46	M36 X 2.0	20.3 X 2.4
FEGE 30-SR	Heavy-250 Bar	30	1 1/4	26.5	69	55	50	M42 X 2.0	25.3 X 2.4
FEGE 38-SR	Heavy-250 Bar	38	1 1/2	28.5	77.5	60	60	M52 X 2.0	33.3 X 2.4

Dimensions given approx., fig. WITH tightened nut

Temp RANGE without pressure reductions

FOR 'O' Ring sealing of NBR (buna N- STD) -35Â° TO +100Â° C, FOR FPM

(Viton - ON request) -25Â° TO +120Â° C.