




HYDROMATIK
connections par excellence

Metric Bite Type Fittings

BO-A BO-A | Connecting Parts for Flare Tube Fittings



Connecting Part	Series	PN Bar	Tube OD	Center Unit With 'O' Rings	Loose Sleeve	Nut
BO-A 06-L	L	500	6	BO-ZR 06-L	BO-DR 06-L	BO-M 06-L
BO-A 08-L	L	500	8	BO-ZR 08-L	BO-DR 08-L	BO-M 08-L
BO-A 10-L	L	500	10	BO-ZR 10-L	BO-DR 10-L	BO-M 10-L
BO-A 12-L	L	400	12	BO-ZR 12-L	BO-DR 12-L	BO-M 12-L
BO-A 15-L	L	400	15	BO-ZR 15-L	BO-DR 15-L	BO-M 15-L
BO-A 18-L	L	400	18	BO-ZR 18-L	BO-DR 18-L	BO-M 18-L
BO-A 22-L	L	250	22	BO-ZR 22-L	BO-DR 22-L	BO-M 22-L
BO-A 28-L	L	250	28	BO-ZR 28-L	BO-DR 28-L	BO-M 28-L
BO-A 35-L	L	250	35	BO-ZR 35-L	BO-DR 35-L	BO-M 35-L
BO-A 42-L	L	250	42	BO-ZR 42-L	BO-DR 42-L	BO-M 42-L
BO-A 06-S	S	630	6	BO-ZR 06-S	BO-DR 06-S	BO-M 06-S
BO-A 08-S	S	630	8	BO-ZR 08-S	BO-DR 08-S	BO-M 08-S
BO-A 10-S	S	630	10	BO-ZR 10-S	BO-DR 10-S	BO-M 10-S

BO-A 12-S	S	630	12	BO-ZR 12-S	BO-DR 12-S	BO-M 12-S
BO-A 14-S	S	630	14	BO-ZR 14-S	BO-DR 14-S	BO-M 14-S
BO-A 16-S	S	630	16	BO-ZR 16-S	BO-DR 16-S	BO-M 16-S
BO-A 20-S	S	400	20	BO-ZR 20-S	BO-DR 20-S	BO-M 20-S
BO-A 25-S	S	400	25	BO-ZR 25-S	BO-DR 25-S	BO-M 25-S
BO-A 30-S	S	400	30	BO-ZR 30-S	BO-DR 30-S	BO-M 30-S
BO-A 38-S	S	400	38	BO-ZR 38-S	BO-DR 38-S	BO-M 38-S

Dimensions given approx.

Temp RANGE without pressure reductions

FOR 'O' Ring sealing of NBR (buna N- STD) -35Â° TO +100Â° C, FOR FPM

(Viton - ON request) -25Â° TO +120Â° C.